

CS32 Series Connectors



Overview

Teledyne CCS32/CS32 is a broadband, SPDT, electromechanical, coaxial switch designed to switch a microwave signal from a common input to either of two outputs. The small switches incorporate Type N or TNC connectors. for use with for use with the CS32 charge bases, able to charge up to 12 cascade devices. Region-specific power cord needs to be ordered separately. CS32 standard rechargeable. The below portal is hosted by CADENAS Technologies AG and its subsidiaries and affiliated companies (including CADENAS Konstruktions Softwareentwicklungs und Vertriebs GmbH) (together, "CADENAS"), who are appointed to display the below images relating to Smiths Interconnect products and transfer. CS32 DMC Tools RF Connector Tools CONNECTOR SOCKET 2. 64 datasheet, inventory, & pricing.



Article Content

Amphenol Connectors | Cable Assemblies

Amphenol Communications Solutions (ACS), a division of Amphenol Corporation, is a world leader in interconnect solutions for Communications,

C Series Configurator

The below portal is hosted by CADENAS Technologies AG and its subsidiaries and affiliated companies (including CADENAS Konstruktions Softwareentwicklungs und Vertriebs GmbH) (together,

Teledyne Relays CCS-32N10 Coaxial RF Switch, SPDT, Type N,

Teledyne CCS32/CS32 is a broadband, SPDT, electromechanical, coaxial switch designed to switch a microwave signal from a common input to either of two outputs. The small switches incorporate Type

CS32 | Ultra-Low Loss 5mm diameter, Double

Panorama's C32 cable is an ultra-low loss 5mm diameter, double-screened, solid center (FRZH) cable that offers great attenuation performance up to 6GHz,

Connection & Mold Selector

Continental Industries is a proud member of the Hubbell family. © 2018 Hubbell. All Rights Reserved.

Series CCS-32/CS-32 COAX SWITCHES Failsafe SPDT Coaxial Switch

Date Code All switches are marked with either a unique serial number or a date code. Date codes are in accordance with MIL-STD-1285 Paragraph 5.2.5 and consist of four digits. The first two digits define

CCS-32 FAILSAFE

All switches are marked with either a unique serial number or a date code. Date codes are in accordance with MIL-STD-1285 Paragraph 5.2.5 and consist of four digits.

Series CCS-32/CS-32 COAX SWITCHES Latching SPDT Coaxial Switch

ENVIRONMENTAL AND PHYSICAL CHARACTERISTICS Operating Temperature
Commercial Model, CCS-32 Elite Model, CS-32

CS Series Connectors – Mouser

CS Series Connectors are available at Mouser Electronics. Mouser offers inventory, pricing, & datasheets for CS Series Connectors.

CS32 DMC Tools | Mouser

CS32 DMC Tools RF Connector Tools CONNECTOR SOCKET 2.64 datasheet, inventory, & pricing.

CS32 DANIELS, CONNECTOR SOCKET (2.640) | Newark Electronics

Buy CS32 - DANIELS - CONNECTOR SOCKET (2.640). Newark Electronics offers fast quotes, same day dispatch, fast delivery, wide inventory, datasheets & technical support.

Panorama Antennas CS32

The CS32 is built to withstand a wide range of environmental conditions, offering consistent performance from -30 °C to 80 °C. Its versatile connectors, a female N connector and a male SMA connector,

Panorama Antennas CS32 | Overview, Specs, Details | SHI

Discover the exceptional performance and reliability of the Panorama Antennas CS32 antenna cable. Engineered for demanding network environments, this cable features a halogen-free design,

Teledyne Relays CCS-32N10-S Relay,E-Mech,Coaxial

Teledyne - CCS32 SeriesTeledyne CCS32/CS32 is a broadband, SPDT, electromechanical, coaxial switch designed to switch a microwave signal from a common input to either of two outputs. The

Panorama CS32

Designed with a silicone rubber gasket, the Panorama CS32 offers low loss performance and durability, making it an ideal choice for various environmental conditions. Versatile compatibility Equipped with

CS32 Quick Start Guide

CS32 series mobile computers are designed for use with CS32 charging accessories. For more information, see the CS32 Series Accessory Guide available for download at

DATALOGIC AUTOMATION

CS SERIES The CS series offers high-quality connectors, developed to guarantee maximum reliability with particularly compact dimensions in the standard M8x1 and M12x1 formats, can be used to

Series CCS-32/CS-32 COAX SWITCHES Latching SPDT Coaxial Switch

Please contact Teledyne Coax Switches for derating factors when applications do not meet the foregoing reference conditions.

CS32 Accessories Guide | Honeywell

CS32 cascade power cable, used to connect and cascade multiple charging bases.
CS32 standard rechargeable battery pack, 3.635 V, 6700mAh. Multi-purpose screw driver for USB interface, power

MAP 16 CS32 ILME

ILME MAP 16 CS32 | Enclosure for connectors: HDC; size 77.27; for double latch - This product is available in Transfer Multisort Elektronik. Check out our wide range of products.

Contact Us

For more information, pricing, or custom solutions, please contact us:

Website: <https://www.tomor.eu>

Email: info@tomor.eu

Phone: +49 69 2381 5497

Address: Am Hauptbahnhof 10, 60329 Frankfurt am Main, Germany

This document is for informational purposes only. Specifications subject to change without notice.

