

Can aggregation switches be configured with VLANs



AI Overview

Yes, aggregation switches typically need VLAN configuration if they are handling traffic from multiple broadcast domains or if VLAN tagging is required for link aggregation. Role of VLANs in Aggregation Switches Aggregation switches combine traffic from multiple access switches or servers, often using link aggregation (LACP, EtherChannel, or NIC teaming) to increase bandwidth and provide redundancy. When multiple VLANs exist on the network, the aggregation switch must be aware of these VLANs to properly forward traffic. VLANs allow the switch to separate traffic logically, maintain broadcast domains, and ensure that traffic from different VLANs does not mix. VLAN Tagging and Trunks To carry multiple VLANs over a single aggregated link, the switch ports are configured as trunk ports with VLAN tagging (IEEE 802.1Q). Each VLAN is assigned a tag, and the aggregation switch forwards traffic based on these tags. Without VLAN configuration, the switch cannot distinguish between traffic from different VLANs, which can lead to broadcast storms or misrouted packets. When VLANs May Not Be Required If the aggregation switch is only connecting devices within a single VLAN or a flat network, VLAN configuration is not strictly necessary. In such cases, the aggregated links can operate as untagged ports, and all traffic is treated as belonging to the same broadcast domain. However, this is uncommon in enterprise or data center environments, where multiple VLANs are used for management, storage, production, and backup traffic. Best Practices Configure VLANs on all aggregation switch ports that connect to access switches or servers carrying multiple VLANs. Use trunk ports for aggregated links to carry multiple VLANs simultaneously. Ensure VLAN consistency across all switches in the aggregation topology to prevent misconfigurations and traffic loss. Consider VLAN aggregation (...)

Article Content

VLAN Aggregation Configuration

VLAN aggregation, also called super-VLAN, partitions a broadcast domain on a physical network into multiple VLANs (sub-VLANs) and aggregates them into a single logical VLAN (super-VLAN).

Wired Aggregation | Validated Solution Guide

The services aggregation switches contain a similar set of VLANs as the aggregation switches, but they do not contain access point management VLANs. Additionally, they include a

Port Aggregation Configurations

Port aggregation allows you to group multiple physical ports into one unit. Port aggregation is useful for implementing load balancing and provides a redundant link backup. To allow port aggregation, the

RouterOS

RouterOS Documentation This webpage contains the official RouterOS user manual. RouterOS is the operating system of MikroTik devices. Documentation applies for the latest stable

01-04 VLAN AGGREGATION CONFIGURATION

VLAN aggregation allows different sub-VLANs to use IP addresses on the same network segment, but cannot implement Layer 3 forwarding between sub-VLANs. Hosts in different common VLANs can

Can PC1 ping PC2 on same switch with different VLANs?

□□ Time to test your networking brains! Can you crack this VLAN puzzle? Put your networking knowledge to the test with this practical scenario. Look closely at the topology shown in the graphic ...

Bonded VLAN Topology for HyperScale Flex Appliance

All the other VLANs will be used exclusively for data protection operations. The storage pool network is optional during HyperScale Flex Appliance installation. Storage pool IP addresses on different nodes

Deploy HyperScale X Using Bonded VLAN Topology

Verify that the required VLANs have been created on the network switches and that VLAN tagging has been configured correctly. Verify that at least one VLAN is routable and can

Your second Ethernet port isn't about speed — it's about keeping ...

Your network switch has to support link aggregation, and even if you have everything configured right, it may not work as expected.

Cisco Catalyst 3750 Series Switches Data Sheet

Mix-and-Match Switch Types: Pay as You Expand Your Network Stacks can be created with any combination of Cisco Catalyst 3750 and Cisco

VLAN Configuration Guide

VLANs allow you to separate network devices into distinct groups, even if those devices connect to the same physical switch or to different switches. This segmentation enhances network

Overview of VLAN Aggregation

To solve the preceding problem, VLAN aggregation can be used. VLAN aggregation maps each sub-VLAN to a broadcast domain, associates a super-VLAN with multiple sub-VLANs, and assigns only

How to configure VLAN and NIC Teaming step by step

Learn how to configure VLAN and NIC Teaming on Windows, VMware, and Linux, with clear examples, aggregation modes, and network best

EOS 4.36.1F

Arista switches support Multi-Chassis Link Aggregation (MLAG) to logically aggregate ports across two switches. For example, two 10-gigabit Ethernet ports,

The 9 Best Enterprise Network Switches for 2026

Generally speaking, enterprise-level switches are rack-mounted. When used as a backbone switch, it can support over 500 information points.

Camera VLAN Setup Guide 2025 | Secure IP Camera Network

Step-by-step VLAN configuration for IP cameras using 802.1Q, PoE switches, and firewall routing. Secure surveillance network setup with NVR access today now

Huawei CloudEngine S6750-S Series Switches Datasheet

Huawei CloudEngine S6750-S switches are next-generation enterprise-class core and aggregation switches that offer high performance, high reliability, cloud management, and intelligent operations

Troubleshooting virtual machine network connection issues

Verify that the virtual machine portgroup is configured with the correct VLAN ID, and check the switchports connected to the VMNIC allowing that tagged VLAN traffic, for reference

Understanding VLAN Aggregation

VLAN aggregation allows the switch to assign IP addresses to hosts in sub-VLANs according to the actual number of hosts. For example, if sub-VLAN 2 contains only 10 hosts, the switch allocates IP

QFX5200 Switch Datasheet | HPE Juniper Networking UK& I

Two QFX5200 switch models are available: QFX5200-48YEOL: A 10GbE/25GbE data center access switch that offers 48 small form-factor pluggable plus (SFP+) transceiver ports or SFP28 ports and

Secure VLAN configuration: a practical guide and best

VLANs segment the physical network into isolated logical networks, reducing broadcast traffic and improving performance. The correct use of access

Smart Managed Switch Web

With VLANs configured on a switch, users in the same VLAN can communicate with each other, while users in different VLANs are isolated. In this way, different broadcast domains are

VLAN Aggregation

The purpose of VLAN aggregation is to increase the efficiency of IP address space usage. It does this by allowing clients within the same IP subnet to use different broadcast domains while still using the

UniFi VLAN Design | Proven Security | 2M Technology

UniFi VLAN design for commercial security — isolate cameras, access control, and guest Wi-Fi with proven switch and firewall rules from 2M Technology.

Contact Us

For more information, pricing, or custom solutions, please contact us:

Website: <https://www.tomor.eu>

Email: info@tomor.eu

Phone: +49 69 2381 5497

Address: Am Hauptbahnhof 10, 60329 Frankfurt am Main, Germany

This document is for informational purposes only. Specifications subject to change without notice.

